

## Product of the Week

# Round Cylinders DSNU Double-acting - Inch series


*The DSNU round cylinder meets the highest requirements for running characteristics, service life and load carrying ability.*



- Piston  $\varnothing$  5/16" to 2 1/2"
- Stroke lengths up to 20"
- Double-acting
- Extensive range of accessories

**FESTO**

# DSNU Round Cylinders



Inch Series (sizes 5/16" to 2-1/2" bore)



## General Technical Data

Piston Ø [in]	5/16"	3/8"	1/2"	5/8"	3/4"	1"
Pneumatic connection	10-32 UNF	10-32 UNF	10-32 UNF	10-32 UNF	1/8" NPT	1/8" NPT
Piston rod thread	6-32 UNC	6-32 UNC	10-32 UNF	10-32 UNF	5/16-24 UNF	3/8-24 UNF
Constructional design	Piston					
	Piston rod					
	Cylinder barrel					
Cushioning	Flexible cushioning rings at both ends (P)					
	Adjustable air cushioning at both ends (PPV)					
Cushioning length (PPV) [in]				0.47	0.59	0.67
Magnet for position sensing	Optional					

Piston Ø	1-1/4"	1-5/8"	2"	2-1/2"
Pneumatic connection	1/8" NPT	1/4" NPT	1/4" NPT	3/8" NPT
Piston rod thread	3/8 -24	1/2-20	5/8-18	5/8-18
Constructional design	Piston			
	Piston Rod			
	Cylinder barrel			
Cushioning	Flexible cushioning rings at both ends (P)			
	Adjustable air cushioning at both ends (PPV)			
Cushioning length (PPV) [in]	0.75	0.87	1.06	1.06
Magnet for position sensing	Optional			